

Phileo Pro

Code structure

PHILEO PRO's CODE COMPOSITION																	
POSITIONS 1,2,3	FAMILY PREFIX					PHP	Phileo PRO										
POSITION 4,5,6,7	FLUX						00A0	2000 lm									
							00B0	3000 lm									
							00B3	4000 lm									
							00B6	5000 lm									
							00C0	6000 lm									
							00C5	7000 lm									
							00D0	8000 lm									
							00E0	9000 lm									
							00F0	12000 lm									
							00G0	13000 lm									
POSITION 8	POWER SUPPLY PROGRAM						P	Standard Night Cycle									
							F	Fixed									
							N	Nema-Socket									
							D	DALI									
							1	1 - 10 V									
							Z	Zhaga/D4i24V									
							T	TLC PLC									
							R	TLC Radio									
							M	2200K - CRI 70									
							N	2200K - CRI 80									
POSITION 9	CT + CRI						P	2700K - CRI 70									
							Q	2700K - CRI 80									
							H	3000K - CRI 70									
							W	3000K - CRI 80									
							I	4000K - CRI 70									
							L	4000K - CRI 80									
							00E1	Optic E1									
							00L1	Optic L1									
					00W1	Optic W1											
POSITION 14	COLOUR					A	Anthracite										
POSITION 15,16	NB. OF LED (12,18,24,36)					12	12 LED										
POSITION 17	FIXING MODE/APPLICATION					P	Pole										
						Y	Pole Class I										

ESEMPIO: PHILEO PRO su palo 18 LED, antracite 6000 lm - 3000K CRI 80, ottica W1 e DALI

COD.	P	H	P	0	0	C	0	D	W	0	0	W	1	A	1	8	P
POS.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17

Il codice risultante è: **PHP00C0DW00W1A18P**

